

Accreditation Scope

Balance Calibration

LB-CAL-040

PHI Sigma Calibration

407, Habib AG Zurich Bank Building, Bank Street

Bur Dubai, Dubai-United Arab Emirates

Issue no.: 03

Date: 30-11-2020

Valid to: 03-08-2022

Calibration Field/ Measuring Quality	Calibration Method	Range and Specification	Calibration Measurement Capability (CMC)*	Location
Electronic Balance	According to OIML R-76-2006 and cg 18-2015 Using E2 class standard 1 mg - 10 kg	0 to 200 g	0.3 mg	Customer Premises
		> 200 g up to 2 kg	8.3 mg	
		> 2 kg up to 20 kg	90 mg	
	According to OIML R-76-2006 and cg 18-2015 Using M1 class standard 5 kg – 300 kg	> 20 kg to 60 kg	2.8 g	Customer Premises
		> 60 kg to 150 kg	5.8 g	
		> 150 kg to 300 kg	11.1 g	

* Calibration and Measurement Capability (CMC) is the smallest uncertainty of measurement that a laboratory can achieve within its scope of accreditation when performing more or less routine calibrations of nearly ideal measurement standards or nearly ideal measuring equipment. Calibration and Measurement Capabilities represent expanded uncertainties expressed at approximately the 95 % level of confidence, usually using a coverage factor of $k = 2$. The actual measurement uncertainty of a specific calibration performed by the laboratory may be greater than the CMC due to the behavior of the customer's device and to influences from the circumstances of the specific calibration.