

## Accreditation Scope

### Volume Calibration

#### LB-CAL-040

#### PHI Sigma Calibration

407, Habib AG Zurich Bank Building, Bank Street

Bur Dubai, Dubai-United Arab Emirates

Issue no.: 03

Date: 30-11-2020

Valid to: 03-08-2022

Calibration Field/ Measuring Quality	Calibration Method	Range and Specification	Calibration Measurement Capability (CMC)*	Location
Micropipette	Gravimetric Method According to ISO 4787/Euramet Cg-19	10 µl to 100 µl	0.95 µl	Laboratory
		> 100 µl to 1000 µl	1.9 µl	
		> 1000 µl to 10000 µl	20 µl	
Volumetric glass ware, Measuring cylinder Measuring Flask Burettes Pipettes	Gravimetric Method According to ISO 4787 Cg-19	0 to 10 ml	0.08 ml	Laboratory
		> 10 ml to 100 ml	0.48 ml	
		> 100 ml to 2000 ml	3.2 ml	

\* Calibration and Measurement Capability (CMC) is the smallest uncertainty of measurement that a laboratory can achieve within its scope of accreditation when performing more or less routine calibrations of nearly ideal measurement standards or nearly ideal measuring equipment. Calibration and Measurement Capabilities represent expanded uncertainties expressed at approximately the 95 % level of confidence, usually using a coverage factor of  $k = 2$ . The actual measurement uncertainty of a specific calibration performed by the laboratory may be greater than the CMC due to the behavior of the customer's device and to influences from the circumstances of the specific calibration.